

OYPLATM DIY



48" High Lift Jack

USER MANUAL Model No: 3033

Safety Instructions

Notice: Ensure you read and fully understand instructions before use

While every attempt is made to ensure the highest degree of protection in all equipment, we cannot guarantee freedom from injury. The user assumes all risk of injury due to use. All merchandise is sold on this condition, which no representative of the company can waive or change.

- Never carry out any alterations or modifications to this product.
- This product is not a toy, and is only to be used for its designated purpose.
- Only use this product on stable, level and dry ground.
- Ensure that the load is stabilised so that it will not shift when it is being lifted or lowered.
- Ensure the jack won't slip once load has been applied.
- Do not work underneath a vehicle once raised unless you have additional supporting stands.
- Do not push the load off the jack – lower it carefully.
- Do not use handle extensions.
- Do not carry the jack by its handle.
- Leaving the product outside exposed to weather, especially direct sun, rain and salt air, will speed the weathering process. This can be slowed by removing the product from these conditions, or covering it with a suitable cover.
- This product is not intended for use by persons (including children) with reduced physical, sensory and mental capacities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the product by persons responsible for their safety.
- Clean only with a damp cloth. Do not use strong industrial cleaning substances or abrasive materials as these will damage the product.
- If the product is damaged or has any defects, please contact cservice@oypla.com

Operating Instructions

TO RAISE A LOAD

1. Following all safety precautions, place the foot of the jack beneath the load. Lift the reversing latch (17) to its UP position and ensure it is locked in place; with the indentation on the latch firmly engaged in the notch on the reversing switch (18) - refer to Fig. 1.
2. Jack up the nose until it comes into contact with the load at the desired point of lift. Pause at this stage and check to ensure there are no obstacles preventing a clean lift.
3. Pull down firmly and evenly on the handle and observe the load rising. As the handle is pulled down, you will hear the climbing pin (13) click into place as it locates a hole in the steel bar (3). At this point, relax the handle allowing the pin to take the load.
4. Raise the handle to the top of its stroke and repeat step 3 until your desired height is reached.

TO LOWER A LOAD


IMPORTANT: The jack must be loaded with a minimum of 50KG (110LBS) to lower step by step; otherwise the lifting nose will drop.

1. Taking all necessary precautions, take the load with the jack (jack the load up slightly) and ensuring the handle is in the FULL UPRIGHT position.
2. Trip the reversing latch (17) so that it is in the DOWN position; causing the indentation on the latch to become disengaged from the notch on the reversing switch - refer to Fig. 2.
3. Keeping a firm grip on the handle, pull down firmly and evenly on the handle as you would for 'raising a load'.

TO RAISE A LOAD



TO LOWER A LOAD



Please retain a copy of all instructions for future consultation.



An Official Oypla Branded Product