User Manual

OYPLA NOTE OF THE PROPERTY OF



6A 12V Car Battery Charger

CE

USER MANUAL Model No: 3449

Safety Instructions

Notice: Ensure you read and fully understand instructions before use

While every attempt is made to ensure the highest degree of protection in all equipment, we cannot guarantee freedom from injury. The user assumes all risk of injury due to use. All merchandise is sold on

this condition, which no representative of the company can waive or change.

• This product is not a toy, and is only to be used for its designated purpose.

• Never carry out any alterations or modifications to this product.

• This product is intended for use under cover only. This is to avoid the product

becoming wet and creating a higher risk of electrical shock.

This product is for domestic use only.

• Ensure the power supply to the socket into which the appliance is plugged, is in

accordance with the rating label on the appliance and that the socket is earthed.

To protect against electrical shock, do not immerse cord, plug or any part of this

appliance in water or any other liquid.

• This product is not intended for use by persons (including children) with reduced

physical, sensory and mental capacities, or lack of experience and knowledge, unless

they have been given supervision or instruction concerning use of the product by

persons responsible for their safety.

Clean only with a damp cloth. Do not use strong industrial cleaning substances or

abrasive materials as these will damage the product. Make sure the product is off,

unplugged from the socket and been left for five minutes to remove the risk of

electrical shock.

• If the product is damaged or has any defects, please contact cservice@oypla.com

Technical Parameters

Input: AC220-240V 50Hz

Output: DC12V 4.2A

MAX: 6AMP

Operating Instructions

General Introductions

If the battery is over-charged, the charger will keep it at a regular current output.

If a short circuit occurs whilst the charger is in use, the charger will switch itself off and return to normal operation after one to two minutes.

The output current of the charger is stable and offers complete protection to the battery. It only requires three to four hours to charge the battery to full capacity.

To check if the car battery charger is charging correctly, check the current meter or the LED below.

How to Use

- 1. Attach the red alligator clip to the positive terminal on the battery (this is identified by the "+" sign).
- 2. Attach the black alligator clip to the negative terminal on the battery (this is identified by the "-" sign).
- 3. Plug the battery into an earthed power socket. This will cause the car battery to begin charging.
- 4. Unplug both of the alligator clips, ensuring that you only touch the plastic areas of the alligator clips whilst doing this.

Please retain a copy of all instructions for future consultation.









Imported into the EU by Oypla.com LLP, Uxbridge, UB8 2FX

Environmental Protection

Products bearing the symbol shown above means that used electrical and electronic equipment (WEEE) should not be mixed with general household waste. For proper treatment, recovery and recycling, please take this product(s) to designated collection points where it will be accepted free of charge. Disposing of this product correctly will help save valuable resources and prevent any potential negative effects on human health and the environment, which could otherwise arise from inappropriate waste handling. Please contact your local authority for further details of your nearest designated collection point. Penalties may be applicable for incorrect disposal of this waste, in accordance with your national legislation.

USER MANUAL Model No: 3449