



150kg Platform Hand Truck

USER MANUAL Model No: 3791

Safety Instructions

Notice: Ensure you read and fully understand instructions before use

While every attempt is made to ensure the highest degree of protection in all equipment, we cannot guarantee freedom from injury. The user assumes all risk of injury due to use. All merchandise is sold on this condition, which no representative of the company can waive or change.

- Before using the product, make sure all fastenings are tightly in place and that everything is in order.
- Never carry out any alterations or modifications to this product.
- The maximum load capacity of this product is 150kg. DO NOT exceed this capacity.
- The product is designed from pushing, only pull if absolutely necessary.
- Load the platform evenly, ensuring that the weight of the load is balanced towards the centre.
- DO NOT push the truck over rough and uneven ground, or up and down curbs.
 Use ramps where available.
- DO NOT transport loads that will impair your frontal vision, ensuring that the height of the load does not exceed the height of the handle.
- Ensure that the load is stable before moving the truck.
- When transporting heavy loads, make sure that the heaviest part of the load is in direct contact to the platform of the truck and touching the frame.
- Leaving the product outside and exposed to weather, especially direct sunlight, rain and salt air, will speed the wreathing process. This can be slowed by removing the product from these conditions, or covering the product with a suitable cover.
- If the product is damaged or has any defects, please contact cservice@oypla.com

Assembly Instructions

Parts List:

Please check you have all parts below before attempting to assemble this product.

If you are missing any of the below parts, please contact Oypla customer services: cservice@oypla.com

- 1. Attach the wheels by securing to the mounting bolts at each corner. Attach the swivelling wheels to the back of the truck and the static wheels to the front.
- 2. To raise the handle, place your foot on the crossbar along the back of the truck and pull the handle upwards. It will click into place once fully extended. To lower the handle, repeat the process in reverse.

HAVE A QUESTION ABOUT YOUR PURCHASE?

OUR DEDICATED CUSTOMER SERVICES TEAM ARE HAPPY TO HELP CONTACT THEM VIA:

TELEPHONE: 020 3600 2255 EMAIL: cservice@oypla.com LIVE CHAT: www.oypla.com

PLEASE RETAIN A COPY OF THESE INSTRUCTIONS FOR FUTURE CONSULTATION

